

The MegaGuard Easy can measure surface resistance and resistance to the ground of mats, floors and other objects of the EPA area.

> 10 ¹²	1 TΩ - ∞
< 10 ¹²	100 GΩ - 1 TΩ
< 10 ¹¹	10 GΩ - 100 GΩ
< 10 ¹⁰	1 GΩ - 10 GΩ
< 10 ⁹	100 MΩ - 1 GΩ
< 10 ⁸	10 MΩ - 100 MΩ
< 10 ⁷	1 MΩ - 10 MΩ
< 10 ⁶	100 KΩ - 1 MΩ
< 10 ⁵	10 KΩ - 100 KΩ
< 10 ⁴	0-10 KΩ



Resolution:	1 decade
Accuracy:	± 1 decade
Measuring voltage:	10 Vdc for R < 100 kΩ - 100 Vdc for R >100 kΩ
Dimensions:	80 x 120 x 27 mm
Weight:	200 g
Battery:	9 V

Probes and accessories:

- SG9265065: Shielded probe made to IEC 61340-5-1, 63/30mm diameter, 2.5 kg weight
- SG9265070: Concentric ring PROBE made to IEC 61340-5-1, 63/30mm diameter, 2.5 kg weight
- SG9265013B: Connection cable jack 3.5mm - banana 4mm

Scope of supply:

- 1 MegaGuard Easy with battery
- 1 connection cable SG9265013B, 3.5mm jack - banana4mm
- Manual
- ISO9000 traceable calibration certificate.
- Box