

# ■ Vertriebsbüros

Baden-Württemberg ■ Hessen/Rheinland-Pfalz Nordbayern ■ Südbayern ■ Ostdeutschland ■ Österreich

# **Technisches Datenblatt**

Der Inhalt des Datenblattes wurde vom Hersteller übernommen.







# Envi-Ro-Tech™ 1672 Freezer

Freeze Spray **1672** 

#### Introduction

An HFC-134a based, rapidly evaporating liquid that can chill to -62°F (-52°C). Because HFCs do not harm the ozone, this product has a zero ozone depletion factor. Used as a troubleshooting aid for intermittently faulting capacitors, resistors, semi-conductors, and other defective components. It also detects cold solder joints, cracks in printed circuit boards, and oxidized junctions.

### Features / Benefits

Non-Flammable Non-Ozone Depleting Chills to -62°F (-52°C) Zero Residue

# **Chemical Components**

1,1,1,2-Tetrafluoroethane......(811-97-2) 100%

# **Environmental Policy**

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

# **Packaging and Availability**

Envi-Ro-Tech™ 1672 Freezer is available in the following sizes:

1672-10S 10 Ounce Aerosol

#### Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

#### **North America**

Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043

email: tsales@techspray.com

# **Europe**

**Techspray International** UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443 email: tseurope@techspray.com

**Countries Outside US** 

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com English MSDS French MSDS German MSDS Italian MSDS Spanish MSDS

