

■ Vertriebsbüros

Baden-Württemberg ■ Hessen/Rheinland-Pfalz Nordbayern ■ Südbayern ■ Ostdeutschland ■ Österreich

Technisches Datenblatt

Der Inhalt des Datenblattes wurde vom Hersteller übernommen.





Product Information

No-Clean Flux Dispensing Pen

Trace Technologies™ 2507

Introduction

The No-Clean Flux Dispensing Pen is designed to dispense no-clean flux in the high precision applications of prototype and rework/repair of printed circuit boards. The resin and halide-free no-clean flux will leave no residues. It provides optimum wetting over a wide range of surfaces and will not damage commonly used plastics.

Features / Benefits

Excellent Wetting Abilities Pen Tip Allows Accurate Application Excellent for Surfaces with Poor Solderability

Chemical Components

| Isopropanol | (67-63-0) | 90-100% |
|-------------|------------|---------|
| Adipic Acid | (124-04-9) | 2-3% |

Environmental Policy

Techspray® is committed to developing products to ensure a safer and cleaner environment. We will continue to meet and sustain the regulations of all federal, state and local government agencies.

Packaging and Availability

No-Clean Flux Dispensing Pen is available in the following sizes:

2507-N 1 11.5ml Pen

Resources

Techspray® products are supported by a global sales, technical and customer services resources.

For additional technical information on this product or other Techspray® products in the United States, call the technical sales department at 800-858-4043, email tsales@techspray.com or visit our web site at: www.techspray.com.

North America

Tech Spray L.P. P.O. Box 949 Amarillo, TX 79105 800-858-4043 email: tsales@techspray.com

Techspray International UNIT 4, 44/46 Bunyan Road, Kempston Bedford MK42 8HL United Kingdom +44 (0) 1234 855443 email: tseurope@techspray.com

Europe

Countries Outside US

Call to locate a distributor in your country.

Important Notice to Purchaser/User: The information in this publication is based on tests that we believe are reliable. The results may vary due to differences in tests type and conditions. We recommend that each user evaluate the product to determine its suitability for the intended application. Conditions of use are outside our control and vary widely. Techspray's only obligation and your only solution is replacement of product that is shown to be defective when you receive it. In no case will Techspray® be liable for any special, incidental, or consequential damages based on breach of warranty, negligence or any other theory.



Tech Spray, L.P. P.O. Box 949 Amarillo, TX 79105 www.techspray.com English MSDS French MSDS German MSDS Italian MSDS Spanish MSDS

